

CASEMENT WINDOWS

CM 075 SERIES



Windows have been designed and tested to comply with the requirements of the Florida Building Code 2010.

Heavy gauge tubular extrusions are used for high strength properties and durability of aluminum.

Windows designed with laminated glass to be impact resistant and meet stringent hurricane codes.

Exterior glass muntins are available as an option.

CONFIGURATIONS:



Butt Hinges

Max. size: 37" x 63" or Equivalent



Concealed Scissor Hinges

Max. size: 33" (vent width) x 63" or Equivalent

STANDARD SIZES:

24 x 48	30 x 48	42 x 48
24 x 60	30 x 60	48 x 48
24 x 63	30 x 63	
24 x 66	30 x 66	
24 x 72	30 x 72	


MODULAR SIZES

19 1/8 x 38 3/8	19 1/8 x 66	24 x 74 1/4	26 1/2 x 63	30 x 50 5/8	37 x 60	53 1/8 x 38 3/8
19 1/8 x 48	19 1/8 x 72	26 1/2 x 38 3/8	26 1/2 x 66	30 x 74 1/4	37 x 63	
19 1/8 x 50 5/8	19 1/8 x 74 1/4	26 1/2 x 48	26 1/2 x 72	37 x 38 3/8	42 x 38 3/8	
19 1/8 x 60	24 x 38 3/8	26 1/2 x 50 5/8	26 1/2 x 74 1/4	37 x 50 5/8	42 x 50 5/8	
19 1/8 x 63	24 x 50 5/8	26 1/2 x 60	30 x 38 3/8	37 x 48	48 x 38 3/8	

COMMODITY SIZES

 MEETS EGRESS REQUIREMENTS

APPROVED GLASS TYPES:



5/16" Laminated

1/8" H.S. Glass
.090 PVB Interlayer
1/8" H.S. Glass