

SLIDING GLASS DOORS

RS 240 SERIES



Sliding glass door have been designed and tested to comply with the requirements of the Florida Building Code 2010.

Heavy gauge tubular extrusions are used for high strength properties and durability of aluminum.

Laminated or Laminated Insulated glass are impact resistant glasses tested to meet stringent hurricane codes.

Exterior muntins or munitins placed between the insulated/laminated glass are available as an option.


Free standing jambs are available

NFRC thermal tested with qualified glass specifications.


CONFIGURATIONS:




OXXO
Max Panel: 60" x 108"



OXO
Max Panel: 60" x 108"



OXO
Max Panel: 60" x 108"



OX
Max Panel: 60" x 108"




XO
Max Panel: 60" x 108"

STANDARD SIZES:


30 x 80	36 x 80	42 x 80	48 x 80	54 x 80	56 1/2 x 80	60 x 80	66 x 80
30 x 96	36 x 96	42 x 96	48 x 96	54 x 96	56 1/2 x 96	60 x 96	66 x 96
30 x 102	36 x 102	42 x 102	48 x 102	54 x 102	56 1/2 x 102	60 x 102	
30 x 108	36 x 108	42 x 108	48 x 108	54 x 108	56 1/2 x 108	* 60 x 108	

APPROVED GLASS TYPES:




7/16" Laminated

3/16" H.S. Glass
.090 PVB Interlayer
3/16" H.S. Glass



15/16" Lami/Insulated

5/32" Temp Glass
3/8" Air Space
5/32" H.S. Glass
.090 PVB Interlayer
5/32" H.S. Glass



*15/16" Lami/Insulated

5/32" Temp Glass
3/8" Air Space
5/32" Temp Glass
.090 PVB Interlayer
5/32" Temp Glass

Note: Glass may cause distortion